

WOYR2.E77920 Switches, Appliance and Special Use - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

For enhanced search functionality, please visit UL's [iQ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Switches, Appliance and Special Use - Component

[See General Information for Switches, Appliance and Special Use - Component](#)

ECHO ELECTRIC CO LTD

E77920

621 NAGAI

YATSUSHIRO-CHO

FUEFUKI-SHI, YAMANASHI 406-0823 JAPAN

Cat. No.	Amps	V	Frequency	HP
SC-W1, SC-W2	5/3	125/250	60	—
SC-WL	5/3	125/250	60	—
SE-W2	6/4	125/250	60	—
		to GND		
	6	125	60	—
SF,f/b W, /fb/ followed by 1 thru 5, may be f/b F, O, P, R, S, T, f/b numbers, letters.	5/3	125/250	60	—
SG	8/6	125/250	60	—
	6/4	125/250	60	—
SJ	10	250	60	—
SN Series	3	250	60	—

Marking: Company name or trademark "EDK", electrical rating and Recognition Mark on switch or smallest container. If marked on the switch, the catalog number may be provided on the smallest unit container.

Cat. No.	Temp C	POL/THR	Per Pole	Endurance	SPCOA
SC-W1, SC-W2	65	1/1 or 2	—	6K	See Note 1

Note 1: The quick-connect tab has not been tested with a female connector, and the suitability of the combination should be considered in the end-use application.

Cat. No.	Temp C	POL/THR	Per Pole	Endurance	SPCOA
SC-WL	65	1/1 or 2	—	6K	2
SE-W2	65	2/1	—	6K	3, See Notes 1,2,3
SF,f/b W, f/b 1 thru 5, may be f/b F, O, P, R, S, T, f/b numbers, letters.	65	1/1 or 2	—	6K	See Note 3
SG	65	2/1 or 2	PP	10K	See Note 4

	65	2/No or NC	PP	10K	See Note 4
SJ	65	2/1	—	10K	See Note 3
SN Series	85	2/1	PP	6K	—

Note 1: The quick-connect tab has not been tested with a female connector, and the suitability of the combination should be considered in the end-use application.

Note 2: The suitability of the actuator button material as an enclosure has not been investigated.

Note 3: The switches provided with terminals that are to be used for printed circuit board connection have not been investigated as part of this report. The suitability of these terminals should be evaluated for compliance with the end-use product standard.

Note 4: These switches have a contact gap of 3 mm or more.

Last Updated on 2005-08-26

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

? 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: " 2014 UL LLC".